

Equipment of the several versions

Version	Base	Comfort	Luxe	Utility
Monobloc Subframe	●	●	●	●
Manip' monolever (With 2 DA hydraulic distributor; floating position and SA/DA converter)	●	●	-	● ⁽¹⁾
Manip'Drive (With 2 DA hydraulic distributor; floating position and SA/DA converter)	○	○	●	○ ⁽¹⁾
3rd fonction	○	○	○	○
4th fonction	○	○	○	○
HPS (Automatic tool repositioning)	○ ⁽³⁾	○ ⁽³⁾	●	○ ⁽³⁾
PPS Faster (Loader Multicouplers)	○	●	●	○
PPS 2 (Tool Multicouplers)	○	○	○	○
Manip'Activ (Suspension)	○	●	●	-
Euro holder (With automatic tool locking)	●	●	●	●
Manip'Pic bracket (On Euro holder)	●	●	●	●
Manip'Pic (Two tines with integrated box)	○	●	●	○
Hydro-lock (Hydraulic tool locking device)	○	○	○	○
Safety valves (Onlifting and tipping cylinders) (2)	○	○	○	●

● Standard ○ On Option - Not possible

(1) Without floating position and SA/DA converter (2) Not compatible with Manip'Activ suspension and floating position (3) With Manip'Drive

	ORCHARD		COMPACT		STANDARD							
	MP'45A	MP'55A	MP'60A	MP'65A	MP'70A	MP'75A	MP'85A	MP'90A	MP'95A	MP'105A	MP'115A	MP'125A
Tractor power - hp	40 - 80	40 - 80	50 - 80	50 - 80	60 - 90	60 - 90	65 - 100	70 - 110	70 - 110	80 - 125	100 - 140	105 - 150
Lift height tool axis	2m95	3m45	3m45	3m45	*3m77 3m30	*3m77 3m30	*3m77 3m30	3m92	3m92	4m00	4m13	4m27
Lifting capacity on the ground	1750 Kg	2100 Kg	2100 Kg	2100 Kg	*2500 Kg 2775 Kg	*2500 Kg 2775 Kg	*2990 Kg 3200 Kg	2990 Kg	2990 Kg	3400 Kg	3200 Kg	4200 Kg
Lifting capacity at maxi. height	1390 Kg	1510 Kg	1510 Kg	1510 Kg	*1400 Kg 1550 Kg	*1400 Kg 1550 Kg	*1620 Kg 1800 Kg	1800 Kg	1800 Kg	2050 Kg	2030 Kg	2600 Kg
Lifting capacity pallet stacker on the ground	1450 Kg	1770 Kg	1240 Kg	1770 Kg	*1770 Kg	*2100 Kg	*2450 Kg	1900 Kg	2350 Kg	2680 Kg	2500 Kg	3200 Kg
Lifting capacity pallet stacker at 2m	1250 Kg	1240 Kg	1050 Kg	1240 Kg	*1150 Kg	*1500 Kg	*1750 Kg	1420 Kg	1860 Kg	2100 Kg	2300 Kg	2500 Kg
Discharge angle at maxi. height	64°	60°	60°	60°	*53° 70°	*53° 70°	*53° 70°	55°	55°	53°	52°	53°
Excavation angle on the ground	37°	37°	37°	37°	49°	49°	49°	49°	49°	49°	54°	48°
Mechanical self-levelling	Yes	Yes	No	Yes	No	Yes	Yes	No	Yes	Yes	Yes	Yes
DA lift cylinders (ø mm)	ø 65	ø 65	ø 65	ø 65	ø 70	ø 70	ø 75	ø 75	ø 75	ø 80	ø 80	ø 80
Subframe	Gliss Matic	Gliss Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic	Méga Matic
Implement attachment	EURO	EURO	EURO	EURO	EURO	EURO	EURO	EURO	EURO	EURO	EURO	EURO
Manip'Pic (With tines and storage)	Option**	Option**	Option**	Option**	Option**	Option**	Option**	Option**	Option**	Option**	Option**	Option**
Monolever 2 DA	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

Power at 180 bars

*: at the 2nd lift hole

** : option on Basic and Utility versions. Standard on Comfort and Luxe versions.

Note: These features may vary depending on the type of tractor equipped.